



# Carbon Steel Buttweld Fittings

## SPECIAL SCHEDULES

SCHEDULE NO.	NOM. PIPE SIZE IN.	NOMINAL WALL THICKNESS	90° ELBOWS		45° ELBOWS	180° RETURNS		TEES	
			LONG RADIUS	SHORT RADIUS	LONG RADIUS	LONG RADIUS	SHORT RADIUS	FULL SIZE OUTLET	REDUCING OUTLET
LIGHT WEIGHT & S/10	4	.188							
	6	.219							
	8	.219							
	10	.219							
	12	.250							
	14*	.250							
	16*	.250							
20	18*	.250							
	20*	.250							
	24*	.250							
	8	.250							
	10	.250							
30	12	.250							
	14	.312							
	16	.312							
	18	.312							
40	8	.277							
	10	.307							
	12	.330							
	18	.438							
60	12	.406							
	14	.438							
80	8	.406							
	12	.562							
100	10	.593							
	12	.687							
120	8	.593							
	10	.718							
	12	.843							
	4	.438							
140	5	.500							
	6	.562							
	8	.718							
	10	.843							
	12	1.000							
140	8	.812							
	10	1.000							
	12	1.125							

POA

NOTE: \* S10 Fittings are manufactured with taper-bored ends

Reducing Elbow Fittings, Caps and Concentric and Eccentric Reducers in SPECIAL SCHEDULES, SCHEDULE 160 and DOUBLE EXTRA STRONG - Price on Application